



For perfect surfaces even in tight spots. Made in EU.

Random orbital polisher EP/E



The 11mm stroke of the polisher allows for hologram-free polishing on painted and uncoated metal surfaces without heating.

Balanced special motor, powerful, quiet and long-lasting with infinitely variable speed control (full-wave electronics). Quiet planetary gear in die-cast aluminium housing with balanced eccentric sheave for constant polishing. Main housing of glass-fibre reinforced POLYAMIDE with soft component.

Securely stored in stylish case made of high-grade POLYPROPYLENE with original equipment for immediate use: Foam backing pad Ø 50 mm with hook and loop fastening, polishing sponge (medium hard), lambswool polishing disc, polishing felt (medium hard), 12 sanding discs K 2000, two-stage SONAX polishing emulsion for refurbishing paintwork (2x 25ml), microfibre cloth and spanner for tool change.

Technical data:

230V. 100W. 800 - 2,800rpm. Eccentric stroke 11mm. Length 270mm. Weight 800g. Insulated to class 2.

NO 28 680



See us on YouTube!



Supplied in a storage box of high-grade polypropylene including the selection of accessories for immediate use.

Accessories for random orbital polisher EP/E

Foam backing pad

With hook and loop fastening. For use with corundum bound sanding discs and sanding fleece.

NO 29 074 Ø 30mm
NO 29 098 Ø 50mm



Polishing

polishing sponges (Ø 50mm)

For applying the polishing emulsion to painted and metal surfaces with subsequent polishing. With hook and loop fastening. Ø 50 x 25mm.

NO 29 092 2 pieces soft (black)
NO 29 094 2 pieces medium (yellow)
NO 29 096 2 Stück pieces hard (white)



Polishing felt, medium hard

For polishing metals (e.g. stainless steel, brass and copper). With hook and loop fastening. Ø 50mm.

NO 28 666 2 pieces



Lambswool polishing disc

Of high quality, dense lambswool for polishing scratch-proof paints. With hook and loop fastening. Ø 50mm.

NO 28 664 2 pieces



Sanding

Super-fine sanding discs


From silicon carbide. For adding finishing touches to paint or removing varnish runs and inclusions. Ø 50mm.

NO 28 667	12 pieces	grit 400
NO 28 668	12 pieces	grit 1,000
NO 28 670	12 pieces	grit 2,000



Flexible sanding pads

Self-adhesive type. Adapts precisely to uneven surfaces due to foam body. Silicon carbide with high durability thanks to backing in a net structure (prevents clogging by dust). Ideal for smart-repair, fine sanding and reworking of 3D printed parts. Ø 50mm.



NO 28 672	6 pieces	grit 1,000
NO 28 674	6 pieces	grit 2,000



Sanding fleece

Self-adhesive type, used for cleaning, matting and sanding of steel, stainless steel and non-ferrous metals. Also used for paint removal. Ø 50mm.

NO 28 554	5 pieces	medium
NO 28 555	5 pieces	fine

